

<b>Model</b>	<b>Verti-Top 1200</b>
Working width	47.2" (1.2m)
Working depth	Up to 1.02" ( 26mm)
Speed	Maximum 7.5 mph (12 km/h)
Weight	794lbs (360 Kg)
Recommended tractor	25 HP with minimum lifting capacity of 400 kg
Collection Hopper Capacity	0.95 cu.ft. (2x 27 litres)
Maximum capacity	64583ft <sup>2</sup> (6000m <sup>2</sup> )
Mesh of sifting screens (Standard supplied)	0.2" x 0.2" (5 mm x 5 mm)
Three-point connection	Cat. 1
Standard items	<ul style="list-style-type: none"> <li>- Easy to change and adjust the jiggging sieve 5 mm x 5 mm (0.2" x 0.2")</li> <li>- Sliding brush</li> <li>- Integrated adjustable rake</li> <li>- 2 waste receptacles</li> <li>- PTO axle</li> </ul>
Optional	Shaking sieves: <ul style="list-style-type: none"> <li>- 0.13" x 0.13" (3.2mm x 3.2mm)</li> <li>- 0.16" x 0.16" (4mm x 4mm)</li> <li>- 0.2" x 0.2" (5 mm x 5 mm)</li> <li>- 0.22" x 0.22" (5.5mm x 5.5mm)</li> </ul>

<b>Model</b>	<b>Verti-Top 1200</b>
	- 0.24" x 0.24" (6mm x 6mm)