

RINK DISC SPREADERS

topdressing

The Rink twin-disc topdressers spread material up to 15m (49ft) wide and successfully operate with wet or dry sand.

Model Rink	Utility Vehicle Model								
	DS550SP walk-in-front	DS550 towed	DS800 towed	DS1200 towed	DS2000 towed	DS3100 towed	DS3800 towed	DS550 for Cushman Turf Truckster	DS800 for J. Deere Progator, Toro Workman + Jacobson XD
Spread width	2 to 12m (6½-40ft) variable		2 to 12m (6½-40ft) variable		2 to 15m (6½-49ft) variable			2 to 12m (6½-40ft) variable	
Spreading thickness	0.5 to 15mm (0.02-0.60")		0.5 to 15mm (0.02-0.60")		0.5 to 15mm (0.02-0.60")			0.5 to 15mm (0.02-0.60")	
Weight	500kg (1102lbs)	420kg (925lbs)	460kg (1012lbs)	490kg (1078lbs)	820kg (1804lbs)	1700kg	1800kg (3960lbs)	320kg (704lbs) incl subframe	440kg (968lbs) incl subframe
Hopper capacity level	0.55cu.m (19½cu.ft)	0.55cu.m (19½cu.ft)	0.8cu.m (28cu.ft)	1.2cu.m (42cu.ft)	2.0cu.m (70cu.ft)	3.1cu.m (105cu.ft)	3.8cu.m (125cu.ft)	0.55cu.m (19½cu.ft)	0.8cu.m (28cu.ft)
Tractor size	selfpropelled, 18hp engine	25hp+: Double acting hydraulic valve and min. oil supply of 25lt/min by 140 bar (2031psi)	25hp+:	25hp+:	35hp+:	40hp with double acting hydraulic valve and min.oil supply of 25lt/min by 140 bar (2031psi)	60hp+ single acting valve or brake valve PTO driven	utility vehicle with oil pump with min.oil supply of 25lt/min by 140 bar (2031psi)	
Optional items:			Conveyor belt		Conveyor belt			Conveyor belt	

DS550SP walk-in-front



This new top dresser contains a 18hp engine and spreads topdressing material up to 12 meters wide

Disc Spreaders towed



Optional: an electrical control panel, carried to the operator seat, controls the belt and spinner speed

These disc spreaders have a hopper capacity of 0.55m³, 0.8m³ and 1.2m³ (level). The operation of the belt and spinners is done from the tractor seat.